



Saugbrugs NorSC Lite

End Use: NorSC Lite is a product suited for magazines, inserts, catalogues, direct mail and door drop

Basic properties		(nominal values)					
Basis Weight	lbs	ISO 536	28.4	30.4	32	35.1	37.8
Structural properties		(nominal values)					
Thickness	µm	ISO 534	41	43	44	47	50
Density	kg/m ³	ISO 534	1030	1060	1080	1100	1120
Bulk	cm ³ /g	ISO 534	0.97	0.94	0.93	0.91	0.89
Smoothness PPS 10	µm	ISO 8791-4	1.3	1.3	1.2	1.2	1.2
Gloss (Hunter)	%	ISO 8254-1	35	38	41	43	44
Optical properties (D65/10°)		(nominal values)					
Brightness	%	ISO 2470	69	69	69	69	69
Whiteness	%	ISO 11475	52	52	52	52	52
Opacity	%	ISO 2471	89	90	91	93	94
L-value D65	D65/10°	ISO 5631-2	88	88	88	88	88
a-value D65	D65/10°	ISO 5631-2	-1.4	-1.4	-1.4	-1.4	-1.4
b-value D65	D65/10°	ISO 5631-2	4.7	4.7	4.7	4.7	4.7
Printing method		Heat Set Web Offset & Rotogravure					

PRODUCT FAMILY: NorSC, NorSC Lite, Nor SC Cat, NorSC Value	FINISH: Gloss	Norske Skog Saugbrugs is certified according to:
PRINTING METHOD: Heat set web offset	PRODUCER: Saugbrugs	Paper Profile 2014 PEFC FSC EU Timber Regulation ISO 50001: 2011 ISO 9001: 2008 ISO 14001: 2004 EU Ecolabel

Future on Paper

All wood used in
Norske Skog's paper
product originates
from sustainable
managed forests.